## TIRE DIMENSIONS

# **HOOKLESS** / TUBELESS STRAIGHT SIDE (TSS) RIMS

| TIRE WIDTH (A) | | RIM INNER WIDTH (B) [mm] | | | | | |
|---|---|---|---|---|---|---|---|
| mm | inch | 23 - 25 | 26 - 27 | 28 - 30 | 31 - 35 | 36 - 40 | 76 |
| 30 | 1.20 | | | | | | |
| 32 | 1.25 | | | | | | |
| 34 | 1.35 | | | | | | |
| 36 | 1.40 | | | | | | |
| 38 | 1.50 | | | | | | |
| 41 | 1.60 | | | | | | |
| 43 | 1.70 | | | | | | |
| 47 | 1.85 | | | | | | |
| 50 | 2.00 | | | | | | |
| 52 | 2.00 | | | | | | |
| 53 | 2.10 | | | | | | |
| 56 | 2.20 | | | | | | |
| 60 | 2.40 | | | | | | |
| 64 | 2.50 | | | | | | |
| 66 | 2.60 | | | | | | |
| 69 | 2.70 | | | | | | |
| 71 | 2.80 | | | | | | |
| 75 | 3.00 | | | | | | |
| 85 | 3.30 | | | | | | |
| 96 | 3.70 | | | | | | |
| 102 | 4.00 | | | | | | |
| 110 | 4.30 | | | | | | |
| 115 | 4.50 | | | | | | |
| 122 | 4.80 | | | | | | |
| 127 | 5.00 | | | | | | |




= Recommended combination = Possible combination

(A) Refer to tire labelling Example: **25**-622
(B) Refer to rim labelling Example for hookless / tubeless straight side (TSS) rims: 622 x **24** TSS

For conventional tire systems (tube type, tubeless ready and tubeless)

hookless (TSS)

Follow the tire manufacturer's pressure recommendations and never exceed the maximum pressure marked on the tire.
Only mount tires labeled "tubeless" (TL) or "tubeless ready" (TLR) on hookless / tubeless straight side (TSS) rims.
These tires can be mounted either with or without an inner tube.

# **HOOKED** / TUBELESS CROTCHET (TC) RIMS

| TIRE WIDTH (A) | | RIM INNER WIDTH (B) [mm] | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | 15 - 17 | 18-20 | 21 - 22 | 23 - 25 | 26 - 27 | 28 - 30 | 31 - 35 | 36 - 40 | 76 |
| 20 | 0.80 | | | | | | | | | |
| 23 | 0.90 | | | | | | | | | |
| 25 | 1.00 | | | | | | | | | |
| 26 | 1.00 | | | | | | | | | |
| 28 | 1.10 | | | | | | | | | |
| 29 | 1.15 | | | | | | | | | |
| 30 | 1.20 | | | | | | | | | |
| 32 | 1.25 | | | | | | | | | |
| 34 | 1.35 | | | | | | | | | |
| 35 | 1.40 | | | | | | | | | |
| 36 | 1.40 | | | | | | | | | |
| 38 | 1.50 | | | | | | | | | |
| 41 | 1.60 | | | | | | | | | |
| 43 | 1.70 | | | | | | | | | |
| 47 | 1.85 | | | | | | | | | |
| 50 | 2.00 | | | | | | | | | |
| 52 | 2.00 | | | | | | | | | |
| 53 | 2.10 | | | | | | | | | |
| 56 | 2.20 | | | | | | | | | |
| 60 | 2.40 | | | | | | | | | |
| 64 | 2.50 | | | | | | | | | |
| 66 | 2.60 | | | | | | | | | |
| 69 | 2.70 | | | | | | | | | |
| 71 | 2.80 | | | | | | | | | |
| 75 | 3.00 | | | | | | | | | |
| 85 | 3.30 | | | | | | | | | |
| 96 | 3.70 | | | | | | | | | |
| 102 | 4.00 | | | | | | | | | |
| 110 | 4.30 | | | | | | | | | |
| 115 | 4.50 | | | | | | | | | |
| 122 | 4.80 | | | | | | | | | |
| 127 | 5.00 | | | | | | | | | |




= Recommended combination = Possible combination

(A) Refer to tire labelling Example: **25**-622
(B) Refer to rim labelling Example for hooked / tubeless crotchet (TC) rims:: 622 x **18**TC

For conventional tire systems (tube type, tubeless ready and tubeless)

hooked (TC)

Follow the tire manufacturer's pressure recommendations
and never exceed the maximum pressure marked on the tire!